



SDR10P26NK3



SDR10S26N3



SDR6P26N3



SDR10P25R3

Drills



Model Number	Free Speed	Chuck Capacity		Weight		Length		Side to Center		Air Consumption		Sound Level	Spindle Thread
	rpm	in.	mm	lb.	kg	in.	mm	in.	mm	scfm	l/s	dB(A)	
Pistol Grip Non-Reversing Drills (1.0 HP)													
SDR10P60N2	6,000	1/4	6	2.30	1.05	6.5	165	0.8	20	30	14.2	80	3/8"-24
SDR10P60N3	6,000	3/8	10	2.45	1.10	7.0	180	0.8	20	30	14.2	80	3/8"-24
SDR10P40N2	4,000	1/4	6	2.30	1.05	6.5	165	0.8	20	30	14.2	80	3/8"-24
SDR10P40N3	4,000	3/8	10	2.45	1.10	7.0	180	0.8	20	30	14.2	80	3/8"-24
SDR10P26N2	2,600	1/4	6	2.30	1.05	6.5	165	0.8	20	30	14.2	80	3/8"-24
SDR10P26N3	2,600	3/8	10	2.45	1.10	7.0	180	0.8	20	30	14.2	80	3/8"-24
SDR10P26N4	2,600	1/2	13	2.90	1.30	7.5	190	0.8	20	30	14.2	80	1/2"-20
SDR10P12N3	1,200	3/8	10	2.90	1.30	8.0	205	0.8	20	30	14.2	80	3/8"-24
SDR10P7N3	700	3/8	10	2.90	1.30	8.0	205	0.8	20	30	14.2	80	1/2"-20
SDR10P7N4	700	1/2	13	3.30	1.50	8.5	215	0.8	20	30	14.2	80	1/2"-20
SDR10P4N3	400	3/8	10	2.90	1.30	8.0	205	0.8	20	30	14.2	80	1/2"-20
SDR10P4N4	400	1/2	13	3.30	1.50	8.5	215	0.8	20	30	14.2	80	1/2"-20
Pistol Grip Non-Reversing Keyless Chuck Drills (1.0 HP) with Röhm Chucks													
SDR10P60NK3	6,000	3/8	10	2.85	1.30	7.6	195	0.8	20	30	14.2	80	3/8"-24
SDR10P40NK3	4,000	3/8	10	2.85	1.30	7.6	195	0.8	20	30	14.2	80	3/8"-24
SDR10P26NK3	2,600	3/8	10	2.85	1.30	7.6	195	0.8	20	30	14.2	80	3/8"-24
SDR10P26NK4	2,600	1/2	13	3.15	1.40	8.1	210	0.8	20	30	14.2	80	1/2"-20
SDR10P12NK3	1,200	3/8	10	3.30	1.50	8.6	220	0.8	20	30	14.2	80	3/8"-24
SDR10P7NK4	700	1/2	13	3.55	1.60	9.1	230	0.8	20	30	14.2	80	1/2"-20
SDR10P4NK4	400	1/2	13	3.55	1.60	9.1	230	0.8	20	30	14.2	80	1/2"-20
Pistol Grip Reversing Drills (1.0 HP)													
SDR10P40R2	4,000	1/4	6	2.40	1.10	7.1	180	0.8	20	30	14.2	80	3/8"-24
SDR10P40R3	4,000	3/8	10	2.55	1.15	7.6	195	0.8	20	30	14.2	80	3/8"-24
SDR10P25R2	2,500	1/4	6	2.40	1.10	7.1	180	0.8	20	30	14.2	80	3/8"-24
SDR10P25R3	2,500	3/8	10	2.55	1.15	7.6	195	0.8	20	30	14.2	80	3/8"-24
SDR10P20R2	2,000	1/4	6	2.40	1.10	7.1	180	0.8	20	30	14.2	80	3/8"-24
SDR10P20R3	2,000	3/8	10	2.55	1.15	7.6	195	0.8	20	30	14.2	80	3/8"-24
SDR10P20R4	2,000	1/2	13	3.00	1.35	7.9	200	0.8	20	30	14.2	80	1/2"-20
SDR10P7R3	700	3/8	10	3.10	1.40	8.6	220	0.8	20	30	14.2	80	3/8"-24
SDR10P7R4	700	3/8	10	3.55	1.60	9.1	230	0.8	20	30	14.2	80	1/2"-20
SDR10P5R3	500	3/8	10	3.10	1.40	8.6	220	0.8	20	30	14.2	80	1/2"-20
SDR10P5R4	500	1/2	13	3.55	1.60	9.1	230	0.8	20	30	14.2	80	1/2"-20
SDR10P3R3	300	3/8	10	3.10	1.40	8.6	220	0.8	20	30	14.2	80	1/2"-20
SDR10P3R4	300	1/2	13	3.55	1.60	9.1	230	0.8	20	30	14.2	80	1/2"-20
Inline Non-Reversing Drills (1.0 HP)													
SDR10S60N2	6,000	1/4	6	2.20	1.00	7.8	200	0.8	19	30	14.2	78	3/8"-24
SDR10S60N3	6,000	3/8	10	2.30	1.05	8.3	210	0.8	19	30	14.2	78	3/8"-24
SDR10S40N2	4,000	1/4	6	2.20	1.00	7.8	200	0.8	19	30	14.2	78	3/8"-24
SDR10S40N3	4,000	3/8	10	2.30	1.05	8.3	210	0.8	19	30	14.2	78	3/8"-24
SDR10S26N2	2,600	1/4	6	2.20	1.00	7.8	200	0.8	19	30	14.2	78	3/8"-24
SDR10S26N3	2,600	3/8	10	2.30	1.05	8.3	210	0.8	19	30	14.2	78	3/8"-24
SDR10S12N3	1,200	3/8	10	2.75	1.25	9.3	235	0.8	19	30	14.2	78	3/8"-24
SDR10S7N3	700	3/8	10	2.75	1.25	9.3	235	0.8	19	30	14.2	78	1/2"-20
SDR10S4N3	400	3/8	10	2.75	1.25	9.3	235	0.8	19	30	14.2	78	1/2"-20
SDR10S4N4	400	1/2	13	3.20	1.45	9.8	250	0.8	19	30	14.2	78	1/2"-20



Drills Continued

Model Number	Free Speed	Chuck Capacity		Weight		Length		Side to Center		Air Consumption		Sound Level	Spindle Thread
	rpm	in.	mm	lb.	kg	in.	mm	in.	mm	scfm	l/s	dB(A)	
Pistol Grip Non-Reversing Drills (0.6 HP)													
SDR6P60N2	6,000	1/4	6	2.10	0.95	5.8	145	0.8	20	25	11.8	80	3/8"-24
SDR6P60N3	6,000	3/8	10	2.25	1.00	6.3	160	0.8	20	25	11.8	80	3/8"-24
SDR6P40N2	4,000	1/4	6	2.10	0.95	5.8	145	0.8	20	25	11.8	80	3/8"-24
SDR6P40N3	4,000	3/8	10	2.25	1.00	6.3	160	0.8	20	25	11.8	80	3/8"-24
SDR6P26N2	2,600	1/4	6	2.10	0.95	5.8	145	0.8	20	25	11.8	80	3/8"-24
SDR6P26N3	2,600	3/8	10	2.25	1.00	6.3	160	0.8	20	25	11.8	80	3/8"-24
SDR6P26N4	2,600	1/2	13	2.70	1.20	6.6	170	0.8	20	25	11.8	80	1/2"-20
SDR6P12N3	1,200	3/8	10	2.70	1.20	7.3	185	0.8	20	25	11.8	80	3/8"-24
SDR6P7N3	700	3/8	10	2.70	1.20	7.3	185	0.8	20	25	11.8	80	1/2"-20
SDR6P7N4	700	1/2	13	3.10	1.40	7.8	200	0.8	20	25	11.8	80	1/2"-20
SDR6P4N3	400	3/8	10	2.70	1.20	7.3	185	0.8	20	25	11.8	80	1/2"-20
SDR6P4N4	400	1/2	13	3.10	1.40	7.8	200	0.8	20	25	11.8	80	1/2"-20
Pistol Grip Non-Reversing Keyless Chuck Drills (0.6 HP) with Röhms Chucks													
SDR6P60NK3	6,000	3/8	10	2.45	1.10	6.9	175	0.8	20	25	11.8	80	3/8"-24
SDR6P40NK3	4,000	3/8	10	2.45	1.10	6.9	175	0.8	20	25	11.8	80	3/8"-24
SDR6P26NK3	2,600	3/8	10	2.45	1.10	6.9	175	0.8	20	25	11.8	80	3/8"-24

Signature Series Drill Features



- 1 Available keyed or keyless chuck
- 2 3 planet gear system for increased life and load capacity
- 3 Ring gear
- 4 Ball bearing construction throughout
- 5 Precision machined steel motor
- 6 Teasing throttle
- 7 Cast aluminum handle with comfort grip

Serviceability

- Ring gear is machined into the motor retainer for ease of assembly and disassembly.
- Planetary gear reduction assembly can be serviced without removing the chuck.
- Rotor pinion is case hardened to resist wear.
- Rotor, cylinder and endplates are interchangeable between different models. This reduces the number of spare parts tool cribs need to stock.
- Tipper valve and valve seat are easily accessible for service.